


+49 6239 - 99 78 20
office@arcan.biz



DUROFLEX PU 675

flexible polyurethane coating uv resistance



DuroFlex PU 675 is a crack bridging high performance floor coating. The self-levelling Polyurethane coating is solvent free, suitable for indoor and outdoor application on non- breathable floors. The coating is liquid proof, abrasion and impact resistant. DuroFlex 675 is uv stable and won't change the colour in direct sunlight an additional uv protection is not required. The sister product DuroFlex 670 is not uv stable and changes the colour in direct sunlight.

DUROFLEX PU 675

BENEFIT	APPLICATION	INSTALLATION	ACCESSORIE	PRODUCT INFO
Flexible	Coating – Non-Permeable	Trowel	DuroFlex Primer 671	DOWNLOAD TDS
Crack Bridging	On Asphalt	Squeegee	DuroFlex-678 Pro	REFERENCES
Self-Levelling	On Concrete		Cleaning Agents For Surfaces	
Indoor	On Tiles		HydroSolv 520	
Outdoor	On Existing coatings		Cembond EPW 863	
Liquid Proof			DuroFlex opCoat 677	
UV Stable No Yellowing				

ARCAN GmbH
Kleinniedesheimer Str. 19
D-67240 Bobenheim-Roxheim
Germany

+49 6239 - 99 78 20
office@arcan.biz
arcan.biz

