

+49 6239 - 99 78 20
office@arcan.biz



HYDROBLOC POLYBLEND 540

polymer additive for even better acrylate gel properties



HydroBloc PolyBlend 540 is a reactive polymer additive for HydroBloc Polygel 530. This polymer reacts and cures with the acrylate gel. The use of Polyblend 540 increases mechanical stability, chemical resistance and creates a better gel. The enhanced product comes with a higher solid content than the standard version, which reduces shrinkage in dry conditions. All cases of application, such as the injection building pits, tunnelling or shaft repair are suitable for the use of HydroBloc Polyblend. The polymer additive could replace the water component of HydroBloc Polygel 530 full or partially, depending on the application case.

HYDROBLOC POLYBLEND 540

BENEFIT	APPLICATION	INSTALLATION	ACCESSORIE	PRODUCT INFO
Elasticity	Waterstop	1 Component Pump	Injection Packer	DOWNLOAD TDS
Tear Resistance	Curtain Injection	2 Component Pump	Injection Pumps	REFERENCES
Reduced Shrinkage	Foundation Pit Sealing		Drill Hole Mortar	
	Joint Sealing		Injection Mortar	
	Crack Injection		Waterstop Mortar	
	Canal, Shaft Repair		Hydrox AK 1011	
	Tunnel Injection		HydroBloc Polygel 530	
	Waterproofing Injection		SiliBlend 535.2	

ARCAN GmbH
Kleinniedesheimer Str. 19
D-67240 Bobenheim-Roxheim
Germany

 +49 6239 - 99 78 20
 office@arcan.biz
 arcan.biz

Image not found or type unknown

