

+49 6239 - 99 78 20
office@arcan.biz



HYDROBLOC POLYGEL PU 660

PUR Gel, ready to use with standard 2-comp. pump



HydroBloc Polygel 660 is the only polyurethane gel be processed with a standard 2-component injection pump, with a mixing ratio 1:1. The product is a highly elastic, stable hydrogel. Polygel PU 660 needs permanent humidity and seals joints, cracks, in civil engineering, mining and tunnelling. The gel emulsifies water easily and cures after 50 – 60 seconds into a tear resistant elastic injection gel.

HYDROBLOC POLYGEL PU 660

BENEFIT	APPLICATION	INSTALLATION	ACCESSORIE	PRODUCT INFO
Standard 2 Comp. Pump	Curtain injection	2 Component Pump	Injection Packer	DOWNLOAD TDS
Elastic	Waterstop		Injection Pump 2	REFERENCES
Tear Resistant	Waterproofing Injection		Component	
Fast Curing	Sheet pile wall Sealing		Drill Hole Mortar	
Swellable	Slurry wall Sealing		Injection Mortar	
	Bored pile wall Sealing		Equipment Cleaners	
	Canal, Shaft Repair		Super Stop 615	
	Tunnel Face Consolidation			
	Tunnel umbrella injection			
	Soil, Rock Stabilization			

ARCAN GmbH
Kleinniedesheimer Str. 19
D-67240 Bobenheim-Roxheim
Germany

 +49 6239 - 99 78 20
 office@arcan.biz
 arcan.biz

Image not found or type unknown

