

+49 6239 - 99 78 20
office@arcan.biz



SILOX THIX AGENT

thickening up material for epoxy, polyurethane
and acrylate resins



Silox Thix agents are thickening powders for HydroBloc resins. Silox Thix agents thicken Epoxy, Polyurethane and Acrylate resins. Their use doesn't change the characteristic of the resin. The dosage is very easy and flexible and depends on the actual required thickness. It is possible to create a self-supporting paste which doesn't flow any more, or a medium thick material which won't run out immediately from wide cracks. All stages of thickening are possible. Thickened resins are still pumpable. Silox Thix agent Type 1 is suitable for polyurethane and epoxy resin. Silox Thix agent Type 2 is suitable for epoxy resins and acrylate resins.

SILOX THIX AGENT

BENEFIT	APPLICATION	INSTALLATION	ACCESSORIE	PRODUCT INFO
Easy Dosage Won't Change Material Characteristics	Thickens Resins And Mortars	Stir Into Resin	Injection Systems Cembond EPW 863 Building Casting Resins	DOWNLOAD TDS REFERENCES

ARCAN GmbH
Kleinniedesheimer Str. 19
D-67240 Bobenheim-Roxheim
Germany

+49 6239 - 99 78 20
office@arcan.biz
arcan.biz

