


+49 6239 - 99 78 20
office@arcan.biz



SILOX BAUHARZ 803 NT

low viscosity epoxy resin for building applications
and GFK



Silox Bauharz 803 nt is a perfectly formulated casting and building resin and combines easy handling with low tool stickiness and a 2:1 mixing ratio. Perfect hardening even in thin layers makes it a good choice for coatings, litter layers and adhesive reinforcement. Thin layers cure without surface disturbance and won't leave a sticky surface. Low viscosity and excellent wetting abilities are ideal for high filled mortars e.g. polymer concrete, joint mortars or repair mortars. The excellent mechanical stability and chemical resistance expand the range of applications.

SILOX BAUHARZ 803 NT

BENEFIT	APPLICATION	INSTALLATION	ACCESSORIE	PRODUCT INFO
Mechanical Stability	Litter Layer	Manual	Equipement Cleaners	DOWNLOAD TDS
Chemical Resistance	Scratch Mortar		Duroglass Fleece 1026	REFERENCES
Curing In Thin Layers	Topcoat		Silox Thix Agent	
Low Tool Stickiness	Joint Mortar		Trennfix 480	
Low Allergenic Potential	Primer, Bonding Bridge		Screed Bracket 075	
Excellent Wetting	Polymer Concrete			
	Repair Mortar			
	Adhesive Reinforcement			

ARCAN GmbH
Kleinniedesheimer Str. 19
D-67240 Bobenheim-Roxheim
Germany

 +49 6239 - 99 78 20
 office@arcan.biz
 arcan.biz

Image not found or type unknown

