






BoRox® Paint Stripper 1035

Stripping agent - lacquer, oil paint, synthetic-resin lacquer

BoRox® Paint Stripper 1035 is a high efficient paint stripper and removes most lacquer, oil paint and synthetic-resin lacquer.

BoRox® Paint Stripper 1035 removes old paint and lacquer. BoRox® Paint Stripper 1035 could be used on solvent-proof surfaces and removes paint from wood, metal and mineral surfaces.

	Application with brush, sponge or trowel
	Removes several layers in one step
	Application temperature > 10°C
	No splashing, No dropping
	Easy and efficient

Procedure

1. Preparation:
 - Protect close-by areas
2. Application:
 - Stir the stripping agent well
 - Apply with soft brush
 - wait for app. 4 h, test progress in between
 - Remove the soft layers of paint with a spatula
 - repeat process if necessary
3. Post-treatment:
 - Clean treated areas thoroughly with water and brush
 - wash surface again with clean water
 - let the area dry
 - grind the surface for better adhesion before applying the new paint

Use safety goggles and gloves meanwhile handling BoRox® Paint Stripper 1035. For more detailed safety precautions read our MSDS.

These technical information describe the present-day state of knowledge these product. They should only inform about the possibilities of application and could not release the applicator of his commitment to check the possibility to use the product for the required application. Information for processing can be found in processing instructions of our product. Information about safe handling can be found in our current safety data sheet.

ATI-BoRox® Paint Stripper 1035
© ARCAN GmbH
All rights reserved

ARCAN Waterproof

ARCAN GmbH Spezialbaustoffe

Kleinniedesheimer Strasse 19
D-67240 Bobenheim-Roxheim
Phone: +49 (0)6239 - 99 78 20
Mail: office@arcan.biz
Web: www.arcan.biz

passion to invent 