



GeoRock®185

Fine geomortar for injections

Cement-free, fine geomortar for injections and for grouting cracks and fissured masonry and building material structures.

GeoRock®185 is waterproof, hard, pressure resistant and sets quickly, is frost-resistant and can be loaded early. We recommend GeoRock®185 for repairing damage to concrete, stabilizing damaged geological structures and building materials.

Product data

Composition	Mineral compound, inorganic
pH	> 12,5
Mortar density	1,6 - 1,7 kg/L
Material Shrinkage	< 0,4 mm/m
Compression strength/24h	> 20 N/mm ²
Compression strength/28d	> 50 N/mm ²
Application Data	
Components	2 (Powder und hardener fluid)
Delivered product	Powder (H) in bags a. 20 kg + hardener fluid (F) in cans a 25 kg
Mixing H:F	20 : 25
Grain size	Fine flours ± 10µm
Mixing time	5 minutes, with high speed stirrer
Processing time	25 minutes (mixture in ratio 20 : 25)
Consumption	1,6 - 1,7 kg per mm/m ²
Equipment cleaning	Water



This data sheet is an extract from the product information and should only be used in conjunction with this product information.

Version 2/2020

GeoRock®185 - very simple for the professional !

These technical information describe the present-day state of knowledge these product. They should only inform about the possibilities of application and could not release the applicator of his commitment to check the possibility to use the product for the required application. Information for processing can be found in processing instructions of our product. Information about safe handling can be found in our current safety data sheet.

ATI-GeoRock®185
© ARCAN GmbH
All rights reserved

ARCAN Waterproof

ARCAN GmbH Spezialbaustoffe

Kleinniedesheimer Strasse 19
D-67240 Bobenheim-Roxheim
Phone: +49 (0)6239 - 99 78 20
Mail: office@arcan.biz
Web: www.arcan.biz

passion to invent 