








## Rokryl®Fuge 340 NV

Light-resistant joint sealant for load-carrying sealings in natural and artificial stone

Rokryl®Fuge 340 NV is a UV resistant joint sealant with integrated primer. Due to its low viscosity, Rokryl® distributes itself optimally in the joint gap, which limits its application to horizontal surfaces.

	<b>T-gel 3 Minutes</b>
	<b>UV-resistant</b>
	<b>No primer required</b>
	<b>Peroxide free</b>
	<b>Pleasant odour</b>

The peroxide-free acrylate is almost odourless and has a pleasant odour. The 1:1 mixing ratio allows an easy application by cartridge or, in case of large surfaces, with the ARCAN 2-component pump.

### Application

Rokryl®Fuge 340 NV is already hardened after 3 minutes and can be loaded after another 10 minutes.

Substrates must be clean, load-bearing, dust-free and free of substances that could cause separation. If necessary, we recommend cleaning with our HydroClean® cleaners.

Rokryl®Fuge 340 NV is pure white and does not change colour even in sunlight.

Rokryl®Fuge 340 NV is used for the load-carrying, waterproof grouting of natural and artificial concrete stones.

These technical information describe the present-day state of knowledge these product. They should only inform about the possibilities of application and could not release the applicator of his commitment to check the possibility to use the product for the required application. Information for processing can be found in processing instructions of our product. Information about safe handling can be found in our current safety data sheet.

ATI- Rokryl®Fuge 340 NV|08|2019  
© ARCAN GmbH  
All rights reserved

### ARCAN Waterproof

ARCAN GmbH Spezialbaustoffe

Kleinniedesheimer Strasse 19  
D-67240 Bobenheim-Roxheim  
Phone: +49 (0)6239 - 99 78 20  
Mail: [office@arcan.biz](mailto:office@arcan.biz)  
Web: [www.arcan.biz](http://www.arcan.biz)

passion to invent 