

HYBRIDUR®357

Highly elastic joint sealing

HYBRIDUR®357 is a perfect sealant for joints. The easy to apply product consists of two components, is highly elastic and adheres excellently even to damp substrates. Durable and resistant, it is suitable for many joints. For connection and dilatation joints in building construction and civil engineering, even under permanent water stress.

For application, the two components are mixed and then manually applied within 30-40 minutes from Jekto® Fugenpistole (joint guns), Jekto® Schneckenpumpen (screw pumps) or peristaltic pumps.

If the substrate (joint edges!) is clean and dust-free, no primers or similar are necessary.

The mixed product is a soft paste, but stable and easy and pleasant to use. If necessary, the surface of the fresh grout can be easily smoothed with suitable tools.

The setting time of HYBRIDUR®357 joint sealant depends on the dimension, condition and residual moisture of the substrate and the ambient conditions. In case of larger dimensions, fresh joints should not be exposed to standing water before 7 days.

Fresh dirt with the product, tools and processing equipment can be cleaned with water to which some household detergent has been added.

Properties

Composition PUR-AC hybrid system, solvent-

free, with micronised aggregates

Components

Colour Grey (similar to cement)

Odour Very weak, typical of the product

Density Approx. 0,45 g/l (mixed)

Transport No restrictions

These technical information describe the present-day state of knowledge these product. They should only inform about the possibilities of application and could not release the applicator of his commitment to check the possibility to use the product for the required application. Information for processing can be found in processing instructions of our product. Information about safe handling can be found in our current safety data sheet.

ATI-HYBRIDUR®357 © ARCAN GmbH All rights reserved

ARCAN Waterproof

ARCAN GmbH Spezialbaustoffe

Kleinniedesheimer Strasse 19 D-67240 Bobenheim-Roxheim Phone: +49 (0)6239 - 99 78 20

Mail: office@arcan.biz
Web: www.arcan.biz

