



Spezial Primer A-867 / G-868 / M-869

For difficult substrates and special tasks.





Our special primers are chemical couplers that create a reaction between the substrate and the binder of the coating material.

Primers improve the adhesion on critical substrates. In many cases, a durable connection between the coating/adhesive and the substrate is only possible with the right primer.

Ideally, primers act as chemical couplers and enable connections with enormous strength between substrate and coating. However, such primers are usually not binders in the classical sense and do not form films!

The effect of special primers is based on a reaction between the substrate and the coating. For example, the adhesion of an epoxy resin on smooth glass can be increased by more than a factor of 10 if the right special primer is used.

Benefits

	Ready to use, 1-component product
	Fast drying, fast processing
	Safe application even on damp substrates
	Increased adhesion on tiles and stainless steel

Area of application

Spezial Primer A-867

	Suitable for coatings made of PUR and Epoxy
---	--

Spezial Primer G-868

	Suitable for coatings made of Epoxy
---	--

Spezial Primer M-869

	Suitable for Acrylate and PMMA coatings
---	--

Technical Data	Density	: 0,8 g/ml
	Processing time	: Dries by evaporation, depending on weather conditions and application quantity ~ 20 minutes - 1 h
	Consumption as primer	: 50 - 100 gram/m ²
	Consumption as water- proof bonding agent	:soak the surface thoroughly.

ARCAN special primers are extra strong bonding agents on tiles or stainless steel and are used as a waterproof bonding agent between mineral surfaces and coatings which prevents the formation of bubbles.

These technical information describe the present-day state of knowledge these product. They should only inform about the possibilities of application and could not release the applicator of his commitment to check the possibility to use the product for the required application. Information for processing can be found in processing instructions of our product. Information about safe handling can be found in our current safety data sheet.

ATI-867 / 868 / 869
© ARCAN GmbH
All rights reserved

ARCAN Waterproof

ARCAN GmbH Spezialbaustoffe

Kleinniedesheimer Strasse 19
D-67240 Bobenheim-Roxheim
Phone: +49 (0)6239 - 99 78 20
Mail: office@arcan.biz
Web: www.arcan.biz

passion to invent 