



HydroBloc®Montage Mörtel XL-938

Construction mortar with high strength for sealing, repairing and fixing

Construction Mortar for highest demands in fixing and sealing technique.

The high quality HydroBloc®Montage Mörtel XL-938 is made of 2 components, powder and mixing liquid. The mixing liquid is based on the Cembond® technology made by ARCAN.

The mortar sets fast and cures without cracks. Application is easy. A primer or bonding bridge are not necessary. After setting the result is a safe and sustainable fastening. The material is water- and weatherproof.

Application

- Fastening of machines, windows, bolts, handrails and pipe passages, doorframes
- Trowelling of voids, holes and cracks
- Fixing of screw anchors of suspended ceiling, cupboard and shelf
- For indoor and outdoor
- Minor floor repair

Processing

100 part powder : 34 part component B
t-gel: 2 - 3 minutes, 20°C
complete setting after ~10 minutes, 20°C
Surface must be wetted thoroughly
Do not mix with gypsum or gypsum containing materials

Mix the powder with the B component by hand or stirrer (by weight). After a few seconds the material starts to harden (heat development). Process quickly. Remove excess material immediately.

The underground must be clean, load bearing and free of grease. The leakage area must be opened and deepened to obtain an optimal surface for the application.

The underground and material temperature should be min. + 5° C and max. 35° C. The fresh mortar must be protected from sun and wind.

Machines and tools cleaning is done immediately after working with water or mechanically after hardening.

Storage conditions and shelf life. HydroBloc®Montage Mörtel XL-938 can be stored for at least 6 months in unopened original containers. It should be stored between + 5° C and + 30° C and protected from moisture. The B component is sensitive to frost.

These technical information describe the present-day state of knowledge these product. They should only inform about the possibilities of application and could not release the applicator of his commitment to check the possibility to use the product for the required application. Information for processing can be found in processing instructions of our product. Information about safe handling can be found in our current safety data sheet.

ATI-HydroBloc®Montage Mörtel XL-938 |1|2015
© ARCAN GmbH
All rights reserved

ARCAN Waterproof

ARCAN GmbH Spezialbaustoffe

Kleinniedesheimer Strasse 19
D-67240 Bobenheim-Roxheim
Phone: +49 (0)6239 - 99 78 20
Mail: office@arcan.biz
Web: www.arcan.biz

passion to invent 