






Jekto®Fugenpistole 080

Hand press with battery for integral cartridges type 2!

Jekto®Fugenpistole 080 is used to process type 2 integral cartridges. Jekto®Fugenpistole 080 has a carrying strap for fatigue-free work and a spare battery. The system is immediately ready for use.

	Ideal for small sealing and finishing work
	No time-consuming cleaning
	Time saving
	No machine cleaning during work interruptions
	No problems with temperature during processing

Press equipment

- Battery hand press with hardened piston
- 2 NiMH batteries. Thereby a continuous working is possible
- Safety switch against unintentional switch-on
- Digital battery level indicator at the touch of a button
- High-pressure rubber hose, flexible 70 cm
- Gripping head coupling for taper nipples and flat head nipples for sliding couplings
- Delivery in a practical PVC system case

Technical Features

- 14,4 Volt
- Charger 230 Volt
- Working pressure up to approx. 450 bar
- Battery 1700 mAh
- Charging time approx. 1,5 hours
- Weight of the battery press with battery: approx. 3.3 kg
- Case LxWxH 51x42x10 cm
- Total weight approx. 7 kg

Integral cartridges type 2 are PE cartridges with 400 ml content and a weight of 3.3 kg. The processing is very easy.

Injection Processing

- Remove the cartridge from the foil
- Remove end cap and pull off ring pull cover
- Insert cartridge into the press and screw it on
- Push flat head nipple onto the packer and start injection.

Cleaning

For cleaning, remove the cartridge of HydroBloc®575 Integral and insert a cleaning / preservative cartridge. Now press until the cleaning agent escapes at the end of the hose. Stop the process and leave the system until the next use. Then proceed in reverse order and insert an HydroBloc®575 Integral Type 2 cartridge instead of the cleaning cartridge and start the gun as soon as HydroBloc®575 Integral comes out of the hose connect it to a packer and start the injection.

These technical information describe the present-day state of knowledge these product. They should only inform about the possibilities of application and could not release the applicator of his commitment to check the possibility to use the product for the required application. Information for processing can be found in processing instructions of our product. Information about safe handling can be found in our current safety data sheet.

ATI-Jekto®Fugenpistole 080
© ARCAN GmbH
All rights reserved

ARCAN Waterproof

ARCAN GmbH Spezialbaustoffe

Kleinniedesheimer Strasse 19
D-67240 Bobenheim-Roxheim
Phone: +49 (0)6239 - 99 78 20
Mail: office@arcan.biz
Web: www.arcan.biz

passion to invent 