



Jekto®M-3 and M-4

1 component diaphragm pump - injection pump

Jekto®M-3 and M4 extremely reliable, powerful and handy injection pumps with electric motor. Pumps of the M series are suitable for low and medium viscosity injection resins with sufficient long processing times.

Similar to picture

Easy handling and transport

Advantages

- With electric motor
- Injection pressure continuously adjustable

Special advantages of these very reliable pumps are the low weight, the electric drive and the easy maintenance and handling.

Technical data

Jekto®M-3 / G Jekto®M-4 / T Jekto®M-3 / T		
Pump type	Diaphragm pump	Diaphragm pump
Motor	electric	electric
Max.Delivery	2,2 l/m	4 l/m
Motor power	0,75 kw	1,1 kw
Max. Pressure	220 bar	220 bar
Material reservoir	6 I	6 I
Voltage	230 V AC - 50 Hz	230 V AC - 50 Hz
Weight	Rack M-3 / G: 20 kg Trolley M-3 / F: 23 kg	Trolley M-4 / F: 38 kg
	on frame: 400 x 440 x 500 mm	
	on trolley: 400 x 400 x 600 mm	on trolley: 700 x 500 x 770 mm
Trolley	available	available
Frame	available	-

The machine is supplied complete with 10 m delivery hose and ball valve and is ready for immediate use.

These technical information describe the present-day state of knowledge these product. They should only inform about the possibilities of application and could not release the applicator of his commitment to check the possibility to use the product for the required application. Information for processing can be found in processing instructions of our product. Information about safe handling can be found in our current safety data sheet.

ATI- Jekto®M-3 and M-4 13.03.2020 © ARCAN GmbH All rights reserved

ARCAN Waterproof

ARCAN GmbH Spezialbaustoffe

Kleinniedesheimer Strasse 19 D-67240 Bobenheim-Roxheim Phone: +49 (0)6239 - 99 78 20

Mail: office@arcan.biz
Web: www.arcan.biz

