






BoRox® Paint Stripper 1034

Stripping agent - Dispersion paint, water-based lacquer, synthetic resin mortar

BoRox® Paint Stripper 1034 is a highly efficient paint stripper. It removes emulsion paints, water-based lacquers, synthetic resin mortars.

BoRox® Paint Stripper 1034 removes old paint and lacquer. BoRox® Paint Stripper 1034 could be used on solvent-proof surfaces and removes paint from wood, metal and mineral surfaces.

	Application with brush, sponge or trowel
	Removes several layers in one step
	Application temperature > 10°C
	No splashing, No dropping
	Simple and efficient

Procedure

- | | |
|--------------------|--|
| 1. Preparation: | - Protect close-by areas |
| 2. Application: | - Stir the stripping agent well
- Apply with soft brush
- wait for app. 4 h, test progress in between
- Remove the soft layers of paint with a spatula
- repeat process if necessary |
| 3. Post-treatment: | - Clean treated areas thoroughly with water and brush
- wash surface again with clean water
- let the area dry
- grind the surface for better adhesion before applying the new paint |

Use safety goggles and gloves meanwhile handling BoRox® Paint Stripper 1034. For more detailed safety precautions read our MSDS.

These technical information describe the present-day state of knowledge these product. They should only inform about the possibilities of application and could not release the applicator of his commitment to check the possibility to use the product for the required application. Information for processing can be found in processing instructions of our product. Information about safe handling can be found in our current safety data sheet.

ATI-BoRox® Paint Stripper 1034 12/2017
© ARCAN GmbH
All rights reserved

ARCAN Waterproof
ARCAN GmbH Spezialbaustoffe

Kleinniedesheimer Strasse 19
D-67240 Bobenheim-Roxheim
Phone: +49 (0)6239 - 99 78 20
Mail: office@arcan.biz
Web: www.arcan.biz

passion to invent 